NOMOS LS





- Light suspandable 1x 15" Subwoofer
- Operated by K&F SystemRack or TOPAS
- Frequency range from 33 Hz (-10 dB)
- Very high maximum sound pressure of 128,5 dB (SPL peak/1 m / full space)

The K&F NOMOS LS is a compact and light 15" bass reflex subwoofer with integrated passive high-pass filter. It is particularly appropriate as bass extension for PASSIO, GRAVIS 12 and SCENA 15.

The enclosure has been designed in a discreet look. The speaker front is protected by a grille, underlaid with opaque black foam. Two ergonomic handles on the side panels permit the easy handling of the subwoofer. Three integrated VariPoints[®] allow the quick and safe suspension of the subwoofer by the lifting pin or by an eye bolt.


Thanks to its passive filter, the K&F NOMOS LS may be operated together with the PASSIO, the GRAVIS 12 and the SCENA 15 via an amplifyer channel of the SystemRack or of the TOPAS. In a cluster of 3, cardioid emission is possible with high backward sound attenuation (>30 dB at 80 HZ).


Loudspeaker	
Design	Bass reflex system (K&F SystemRack or K&F TOPAS is required for use)
Crossover frequency (2-way-mode)	100 Hz
Lower cut-off frequency (-3 dB / -10 dB)	40 Hz / 33 Hz
Coverage	Omnidirectional (a cluster of 3 can be driven in cardioid)
Power handling	400 W nominal ¹⁾ 800 W program ²⁾
Max. SPL	128,5 dB (SPL Peak / 1 m / Free Field)
Components	15" long excursion chassis, 75 mm voice coil with double centering, internal and external ventilation, double demodulation ring for minimal distortion
Loudspeaker / Chanal	2
Wiring	(1+/1-) 2 x Speakon [®] 4-pol NLT4MP IN parallel to OUT
Enclosure	
	Frame reinforced enclosure, 15 mm multiplex with highly resilient Polyurea synthetic black coating, 2 ergonomical butterfly handles, 8 non-abrasive plastic sliders, 4 stacking grooves for save stacking of identical enclosures, 3 K&F VariPoint [®] for fast and safe suspension with Lifting Pin or eyebolt, 2 locking profiles for transport optional transport cover, ball-proof steel grille with exchangeable black acoustic foam
Dimensions (W x H x D)	565 x 435 x 510 mm
Weight	25 kg
Accessories	see catalogue or visit www.kling-freitag.de
1) Diale Naice 40, 250 Hz, 2 h , 2) as 1) but with 500/ duty cycle	

¹⁾ Pink Noise 40 - 250 Hz, 2 h ²⁾ as ¹⁾ but with 50% duty cycle









Further information and data like specifications, manuals, technical drawings as DWG, DXF and PDF files as well as data files for acoustic simulations with Ease and Ulysses are available on our web site www.kling-freitag.de

KLING & FREITAG GmbH Junkersstrasse 14 D-30179 Hannover Tel. +49 (0)511 96 99 7-0 Fax +49 (0)511 67 37 94